





- 1 OUTPUT CIRCUIT BREAKER (63A)
- (2) EXTERNAL BATTERY CABINET COM PORTS
- \langle 3 \rangle EXTERNAL BATTERY CABINET CAN PORTS
- \langle 4 \rangle external battery cabinet power connectors
- $\langle 5 \rangle$ address dip switch
- 6 GROUND SCREW

NOTES

- 1. UNIT DIMENSIONS (WxDxH) 430mm x 754mm x 42.5mm (1U) (16.9") x (29.7") x (1.7")
- 2. UNIT WEIGHT: 22kg (48.5lbs)
- 3. SHIPPING DIMENSIONS (WxDxH) 800mm x 1000mm x 285mm 31.4" xx 39.3" x 11.2"
- 4. SHIPPING WEIGHT 48.5kg (106.9lbs)
- 5. MINIMUM AIRFLOW CLEARANCE IS 100mm (4.0") FRONT AND REAR.

() S. 105				
SHEET NO.	DRAWN BY:		DWG. NO.	
2 OF 2	RINU TOMS		GXT5LI_5000-6000GVRT	
CO. NO.	DESIGNED BY:		DATE (LATEST REV.)	
-	PETE BENNER	TITLE OUTLINE DRAWING	2024/04/24	
REF DWG.	APPROVED BY:	LIEBERT GXT5 LITHIUM-ION 5-10kVA	REVISION	505 N. CLEVELAND AVE
_	LUKE JOHNSON	192V EXTERNAL BATTERY CARINET	0	WESTERVILLE, OHIO 43082



Α

В