

- (1) EXTERNAL BATTERY CABINET CAN PORTS
- \langle 2 \rangle external battery cabinet connectors
- (3) OUTPUT CIRCUIT BREAKER (80A)
- 4 GROUND SCREW

NOTES

- 1. UNIT DIMENSIONS (WxDxH) 430mm x 446mm x 42.5mm (1U) (16.9") x (17.5") x (1.7")
- 2. UNIT WEIGHT 9.9kg (21.8lbs)
- 3. SHIPPING DIMENSĬONS (WxDxH) 600mm x 800mm x 297mm (23.6") x (31.5") x (11.7")
- 4. SHIPPING WEIGHT 25.5kg (56.2lbs)
- MINIMUM AIRFLOW CLEARANCE ÍS 100mm (4.0") FRONT AND REAR.

SHEET NO. DRA		DRAWN BY:		DWG. NO.	
	1 OF 1	P BENNER		VEB	CLI-48VRT1U
CO. N	NO.	DESIGNED BY:		DATE (LATEST REV.)	
	-	P BENNER	TITLE OUTLINE DRAWING	2/14/2022	
REF I	DWG.	APPROVED BY:	LIEBERT GXT5LI 1-3kVA	REVISION	1050 DEARBORN DR
	-	N SECORD	48V EXTERNAL BATTERY CABINET	0	P.O. BOX 29186 COLUMBUS, OH 43229



В

Α

2

1

Α

В