Disclosure and photocopying of this document, exploitation and communication of its contents are not permitted, unless permission is expressly granted. All rights are reserved.

REAR VIEW



SIDE VIEW



FRONT VIEW





HARDWIRED TERMINAL DETAIL
(32 A, 1/N/PE, 200–240 V)

AGENCY COMPLIANCE:
- CE-mark: LVD, EMC, RoHS (incl. harmonized standards hereunder)
- CB certification: IEC 60950-1 (2nd)
- BG certification: BV-BG (factory inspected)
- WEEE COMPLIANT

ENVIRONMENTAL RATING:
OPERATING TEMPERATURE: 5 °C – 60 °C (41 °F – 140 °F) NON-CONDENSING, NON-CORROSIVE, 10 % – 90 % RH
STORAGE TEMPERATURE: -20 °C – 85 °C (-4 °F – 185 °F)
MAX. OPERATING ALTITUDE: 3000 m

NOTES:
1. UNIT DIMENSIONS: 1736,5 mm (68,4") H x 50 mm (2.0") D x 56 mm (2.2") W
2. UNIT WEIGHT: 4 kg / 8,8 lbs
3. SHIPPING DIMENSIONS: 2017 mm (79,4") H x 297 mm (11,7") D x 176 mm (7,0") W
4. SHIPPING WEIGHT: 6,8 kg / 15 lbs
5. (2) MOUNTING BUTTONS AND (2) MOUNTING BRACKETS SUPPLIED WITH EACH UNIT. EITHER OPTION CAN BE USED TO MOUNT THE PDU.

OUTPUT POWER

BRANCH	PHASE	RECEPTACLE TYPE (QUANTITY)	VOLTAGE (V)	MAX. CONTINUOUS AMPS (A)	
				PER RECEPTACLE	PER BRANCH
A	L1	12xC13, 3xC19	200–240	10/16	20
B	L1	12xC13, 3xC19, 3xSCHUKO	200–240	10/16/16	20

INPUT POWER

INPUT CORD	INPUT PLUG	WIRE COUNT	FREQUENCY (Hz)	VOLTAGE (V)	RATED AMPS (A)	MAX. CONT. AMPS (A)
–	–	1/N/PE	50/60	200–240	32	32

RoHS COMPLIANT

Dimensions in mm

Rev.	Change	Date	Name
A	18143	07.06.2017	Petrů

Allgemeintoleranzen / General tolerances: –
Oberfläche / Finish: –
Werkstoff / Material: –
Gewicht: / Weight: –

	Date	Name
Drawn	22/10/15	Blass
Checked	22/10/15	Votýpka
Approved	–	–

Bezeichnung / Description: MPH2-EEV_2P3W-32A_24N-6O-3P_HW
Elementary

Zeichnungs-Nr. / Drawing no.: MPE-1560

Maßstab / Scale: 1:5

Verwendet in / Used in: –

Blatt/Sheet: 1/1

VERTIV™

Weitergabe sowie Vervielfältigung dieser Unterlage, Verwertung und Mitteilung ihres Inhalts nicht gestattet, soweit nicht ausdrücklich zugestanden. Alle Rechte vorbehalten.