Disclosure and photocopying of this document, exploitation and communication of its contents are not permitted, unless permission is expressly granted. All rights are reserved.

REAR VIEW



SIDE VIEW



FRONT VIEW



AGENCY COMPLIANCE:

– CB certification:	IEC 60950-1 (2nd)
– CE-mark:	LVD, RoHS (incl. harmonized standards hereunder)
– cCSus certification:	UL 60950-1 (2nd), CSA C22.2 No. 60950-1-07
– BG certification:	BV-BG (factory inspected)
– WEEE COMPLIANT	

ENVIRONMENTAL RATING:
OPERATING TEMPERATURE: 5 °C – 60 °C (41 °F – 140 °F) NON-CONDENSING, NON-CORROSIVE, 10 % – 90 % RH
STORAGE TEMPERATURE: -20 °C – 85 °C (-4 °F – 185 °F)
MAX. OPERATING ALTITUDE: 3000 m

NOTES:
1. UNIT DIMENSIONS: 826.5 mm (32.5") H x 50 mm (2.0") D x 56 mm (2.2") W
2. UNIT WEIGHT: 2.28 kg / 5.0 lbs
3. SHIPPING DIMENSIONS: 1197.0 mm (47.1") H x 297 mm (11.7") D x 176 mm (7.0") W
4. SHIPPING WEIGHT: 4.30 kg / 9.47 lbs
5. (2) MOUNTING BUTTONS AND (2) MOUNTING BRACKETS SUPPLIED WITH EACH UNIT. EITHER OPTION CAN BE USED TO MOUNT THE PDU.

OUTPUT POWER

BANK	PHASE	RECEPTACLE TYPE (QUANTITY)	VOLTAGE (V)	MAX. CONTINUOUS AMPS (A)	
				PER RECEPTACLE	PER BANK
A	L1	18xC13, 3xC19	100-240	10/16	16

INPUT POWER

INPUT CORD	INPUT SOCKET	WIRE COUNT	FREQUENCY (Hz)	VOLTAGE (V)	RATED AMPS (A)	MAX. CONT. AMPS (A)
–	IEC 60320 C20	1/N/PE, 2/PE	50/60	100-240	16	16

RoHS COMPLIANT

Rev.	Change	Date	Name
A	18143	07.06.2017	Petrů

Dimensions in mm

Allgemeintoleranzen / General tolerances: –
Oberfläche / Finish: –
Werkstoff / Material: –
Gewicht / Weight: –

	Date	Name
Drawn	27/10/15	Blass
Checked	27/10/15	Votýpka
Approved	–	–

Bezeichnung / Description: MPH2-EEV_C20-16A_18N-3O
Elementary

Zeichnungs-Nr. / Drawing no.: MPE-3141

Maßstab / Scale: 1:5

Verwendet in / Used in: –

Blatt/Sheet: 1/1

VERTIV™

Weitergabe sowie Vervielfältigung dieser Unterlage, Verwertung und Mitteilung ihres Inhalts nicht gestattet, soweit nicht ausdrücklich zugestanden. Alle Rechte vorbehalten.