



AGENCY COMPLIANCE:

- CE-mark: LVD, RoHS (incl. harmonized standards hereunder)
- CB certification: IEC 60950-1 (2nd)
- BG certification: BV-BG (factory inspected)
- WEEE COMPLIANT

ENVIRONMENTAL RATING:
OPERATING TEMPERATURE: 5 °C – 60 °C (41 °F – 140 °F) NON-CONDENSING, NON-CORROSIVE, 10 % – 90 % RH
STORAGE TEMPERATURE: -20 °C – 85 °C (-4 °F – 185 °F)
MAX. OPERATING ALTITUDE: 3000 m

NOTES:

1. UNIT DIMENSIONS: 1736.5 mm (68.4") H x 50 mm (2.0") D x 56 mm (2.2") W
2. UNIT WEIGHT: 4 kg / 8.8 lbs
3. SHIPPING DIMENSIONS: 2017.0 mm (79.4") H x 297 mm (11.7") D x 176 mm (7.0") W
4. SHIPPING WEIGHT: 6,81 kg / 15 lbs
5. (2) MOUNTING BUTTONS AND (2) MOUNTING BRACKETS SUPPLIED WITH EACH UNIT. EITHER OPTION CAN BE USED TO MOUNT THE PDU.

<div></div> <div>Dimensions in mm</div>				Allgemeintoleranzen General tolerances		Oberfläche Finish		Werkstoff / Material		Gewicht: Weight: —	
				—		—		—			
				Drawn	Date	Name		Bezeichnung / Description MPH2-EEV_4P5W-32A_48N Elementary			
				Checked	27/10/15	Blass					
				Approved	27/10/15	Votýpka					
					—	—		Zeichnungs-Nr. / Drawing no. MPE-1745 Verwendet in / Used in —			
				<div></div> <div>VERTIV™</div>							
A	18143	07.06.2017	Petrù				Maßstab Scale 1:5				
Rev.	Change	Date	Name				Blatt/Sheet 1/1				