



Disclosure and photocopying of this document, exploitation and communication of its contents are not permitted, unless permission is expressly granted. All rights are reserved.

Weitergabe sowie Vervielfältigung dieser Unterlage, Verwertung und Mitteilung ihres Inhalts nicht gestattet, soweit nicht ausdrücklich zugestanden. Alle Rechte vorbehalten.



HARDWIRED TERMINAL DETAIL  
(16 A, 3/N/PE, 200-240/346-415 V)

AGENCY COMPLIANCE:  
- CE-mark: LVD, EMC, RoHS (incl. harmonized standards hereunder)  
- CB certification: IEC 60950-1 (2nd)  
- BG certification: BV-BG (factory inspected)  
- WEEE COMPLIANT

ENVIRONMENTAL RATING:  
OPERATING TEMPERATURE: 5 °C - 60 °C (41 °F - 140 °F) NON-CONDENSING, NON-CORROSIVE, 10 % - 90 % RH  
STORAGE TEMPERATURE: -20 °C - 85 °C (-4 °F - 185 °F)  
MAX. OPERATING ALTITUDE: 3000 m

- NOTES:
- UNIT DIMENSIONS: 1736,5 mm (68,4") H x 50 mm (2,0") D x 56 mm (2,2") W
  - UNIT WEIGHT: 4 kg / 8,8 lbs
  - SHIPPING DIMENSIONS: 2017 mm (79,4") H x 297 mm (11,7") D x 176 mm (7,0") W
  - SHIPPING WEIGHT: 6,8 kg / 15 lbs
  - (2) MOUNTING BUTTONS AND (2) MOUNTING BRACKETS SUPPLIED WITH EACH UNIT. EITHER OPTION CAN BE USED TO MOUNT THE PDU.



OUTPUT POWER

BANK	PHASE	RECEPTACLE TYPE (QUANTITY)	VOLTAGE (V)	MAX. CONTINUOUS AMPS (A)	
				PER RECEPTACLE	PER BANK
A	L1	24xC13, 4xC19	200-240	10/16	16
B	L2	24xC13, 4xC19	200-240	10/16	16
C	L3	24xC13, 4xC19	200-240	10/16	16

INPUT POWER

INPUT CORD	INPUT PLUG	WIRE COUNT	FREQUENCY (Hz)	VOLTAGE (V)	RATED AMPS (A)	MAX. CONT. AMPS (A)
-	-	3/N/PE	50/60	200-240/346-415	16	16

RoHS COMPLIANT

<div></div> <div>Dimensions in mm</div>				Allgemeintoleranzen General tolerances		Oberfläche Finish		Werkstoff / Material		Gewicht: – Weight:			
				–		–		–					
				Drawn	Date	Name		Bezeichnung / Description					
				23/07/2015	Blass		MPH2-EEV_4P5W-16A_36N-12O_HW						
				Checked	–	–		Elementary					
				Approved	–	–							
				<div></div> <div>VERTIV™</div>						Zeichnungs-Nr. / Drawing no.		Maßstab Scale	
										MPE-1161			1:5
A	18143	07.06.2017	Petrú							Verwendet in / Used in		–	
Rev.	Change	Date	Name										1/1