



Disclosure and photocopying of this document, exploitation and communication of its contents are not permitted, unless permission is expressly granted. All rights are reserved.

Weitergabe sowie Vervielfältigung dieser Unterlage, Verwertung und Mitteilung ihres Inhalts nicht gestattet, soweit nicht ausdrücklich zugestanden. Alle Rechte vorbehalten.



HARDWIRED TERMINAL DETAIL
(32 A, 1/N/PE, 200-240 V)

OUTPUT POWER

BRANCH	PHASE	RECEPTACLE TYPE (QUANTITY)	VOLTAGE (V)	MAX. CONTINUOUS AMPS (A)	
				PER RECEPTACLE	PER BRANCH
A	L1	9xSCHUKO	200-240	16	20
B	L1	9xSCHUKO	200-240	16	20

INPUT POWER

INPUT CORD	INPUT PLUG	WIRE COUNT	FREQUENCY (Hz)	VOLTAGE (V)	RATED AMPS (A)	MAX. CONT. AMPS (A)
-	-	1/N/PE	50/60	200-240	32	32

RoHS COMPLIANT

AGENCY COMPLIANCE:



- CE-mark: LVD, EMC, RoHS (incl. harmonized standards hereunder)
- CB certification: IEC 60950-1 (2nd)
- BG certification: BV-BG (factory inspected)
- WEEE COMPLIANT

ENVIRONMENTAL RATING:

OPERATING TEMPERATURE: 5 °C - 60 °C (41 °F - 140 °F) NON-CONDENSING, NON-CORROSIVE, 10 % - 90 % RH
STORAGE TEMPERATURE: -20 °C - 85 °C (-4 °F - 185 °F)
MAX. OPERATING ALTITUDE: 3000 m

NOTES:

- UNIT DIMENSIONS: 1736,5 mm (68,4") H x 50 mm (2,0") D x 56 mm (2,2") W
- UNIT WEIGHT: 4 kg / 8,8 lbs
- SHIPPING DIMENSIONS: 2017 mm (79,4") H x 297 mm (11,7") D x 176 mm (7,0") W
- SHIPPING WEIGHT: 6,8 kg / 15 lbs
- (2) MOUNTING BUTTONS AND (2) MOUNTING BRACKETS SUPPLIED WITH EACH UNIT. EITHER OPTION CAN BE USED TO MOUNT THE PDU.

<div></div> <div>Dimensions in mm</div>				Allgemeintoleranzen General tolerances		Oberfläche Finish		Werkstoff / Material		Gewicht: – Weight: –		
				–		–		–				
				Drawn	Date 22/10/15	Name Blass		Bezeichnung / Description MPH2-EEV_2P3W-32A_18P_HW Elementary				
				Checked	22/10/15	Votýpka						
				Approved	–	–						
				<div></div> <div>VERTIVTM</div>				Zeichnungs-Nr. / Drawing no.			Maßstab Scale	
								MPE-1660			1:5	
A	18143	07.06.2017	Petrů									
Rev.	Change	Date	Name					Verwendet in / Used in			Blatt/Sheet	
								–			1/1	